

AVR models ($\pm 12\%$)
VRp-100000-9339-120M
100KVA
410V $\pm 3\%$
Three phase
VRp-150000-9339-120M
150KVA
410V $\pm 3\%$
Three phase
VRp-200000-9339-120M
200KVA
410V $\pm 3\%$
Three phase

Static voltage regulator with automatic bypass

Precision fast-PWM ac mains voltage correction

TSi Elecpower's VRp is manufactured in a joint venture under license & technology transfer from TSi Power Corporation, USA. This automatic precision voltage regulator allows trouble-free operation of electronic equipment over a very wide mains ac voltage fluctuation range of 180 - 280 V found in many developing countries.

There is no switching of taps or otherwise a break in the power path thanks to continuous pulse-width-modulation (PWM) switching of a buck-boost transformer.

Typical applications

Designed for applications needing absolutely safe and precisely regulated ac power, such as

- Residential & Commercial applications
- Process Industries
- Industrial process controller (PLC)
- Computer Controlled (CNC) Machines
- Medical (MRI, CT) and diagnostics
- Analytical measurement equipment
- Mobile communications (BTS sites)
- Radio / TV broadcasting/Transmission sites

Key VRp Series benefits

VRp is compatible with all loads as it does not switch any components in the power path. VRp's ultra-low impedance assures stability even with the most demanding loads. The automatic bypass assures that connected equipment will not shut down, even if VRp fails.

How the VRp Series works

The high frequency insulated gate bi-polar transistor (IGBT) driven converter takes the incoming ac power, measures against the nominal voltage and adds or subtracts voltage, 20,000 times per second, to achieve precisely regulated 230 vac output.

The automatic bypass will be activated when there is a fault condition. Green LEDs are used to indicate Normal (regulating mode) operation.



Key features of the VRp Series precision voltage regulator

- Outstanding voltage regulation: under standard design voltage range, output regulation will be within $\pm 3\%$, but still higher voltage fluctuation can be covered to achieve liberal regulation within usable output voltage range of 200-250 vac, P-N.
- No switching of active power path
- Fail-safe: automatic bypass
- Instantaneous Correction: boon for CNC Machines & hi-tech electronic gadgets
- Low impedance
- Low weight
- Quiet operation
- Soft switch-on
- Energy efficient



TSi Elecpower (P) Ltd

CIB-212, GIDC Industrial Estate,
Waghodia, Vadodara 391760
Gujarat, India

Ph. : +91 2668 262122
info@tsielecpower.com
www.tsielecpower.com



CATEGORY		VRp series AVR's designed for $\pm 12\%$ fluctuation		
FEATURE	STANDARD THREE PHASE MODELS			
	VRp-100000-9339-120M	VRp-150000-9339-120M	VRp-200000-9339-120M	
ELECTRICAL				
Capacity in KVA (KW)	100 KVA	150 KVA	200 KVA	
Regulator engine	High frequency 20 kHz GBT driven voltage regulation converter			
INPUT				
*Nominal voltage	410 volts ac, three phase			
*Normal operating voltage (typical output regulation within +/- 3% of nominal)	360 - 460 volts ac ($\pm 12\%$) for full regulation			
Relaxed operating voltage (relaxed output regulation within functional range of 200-250V P-N)	305 - 485 volts ac (+18% -25%) within maximum rated input current capacity			
Maximum rated input current	160A	240A	320A	
Nominal frequency	47 - 63 Hz			
Input circuit breaker rating	160 A X 3 phase MCCB	suitably rated MCCB to be provided by client on his incoming connections to VRp		
Input wire size	2x16 mm ² (AWG 6)	2x25 mm ² (AWG 4)	2x35 mm ² (AWG 2)	
Ac connection	Terminal block (L1in , L2in, L3in, neutral and ground wires) provided	3 meter extra incoming wires with lugs provided for connecting to incoming MCCB on client's panel		
OUTPUT				
*Nominal voltage	410 volts ac, three phase			
Power efficiency	typically over 97 % (with 20 - 100% load conditions)			
Voltage regulation (typical, excluding meter error)	+/- 3%			
Maximum rated output current	141 A	211 A	282 A	
System status indicator	Green LED (ON) indicates Normal (regulating mode) operation			
Ac connection	Terminal block (L1in , L2in, L3in, neutral and ground wires) provided	3 meter extra outgoing wires with lugs provided for connecting to outgoing connectors on client's panel		
PHYSICAL				
Dimensions (IN MM) (approx.)	660 Wx 570 H x 660 D	813 Wx 813 H x 813 D	813 Wx 813 H x 813 D	
Weight (approx.)	160 Kgs	300 Kgs	325 Kgs	
Display	Digital output voltage display thru' selector switch			
Annunciation	LED display for Regulation mode, Bypass mode & Fault conditions			
Mounting	4 High Quality Castor wheels, 2 with brakes			
ENVIRONMENTAL				
Ambient temperature	0° to + 45° Centigrade (32° to + 113° Farhenite). 10 to 90% RH non-condensing.			
Cooling method	Fan Cooled			
PROTECTIVE FEATURES				
Standards & Safety	Designed to meet UL 60950-1 standards. Protection class IP 20.			
OV/UV cut off with SPP	Automatic trip in event of High/Low/Missing Voltage, manual reset	Automatic trip signal for client's MCCB in event of High/Low/Missing Voltage, manual reset		
Overload & Short Circuit Protection	Through suitably rated input circuit breaker	Through suitably rated input circuit breaker to be provided by client on his incomer panel		
Soft Switch-On	This feature ensure that output voltage is never higher than input voltage upon switch-on, before it commences full stabilization.			
Automatic bypass	Automatic bypass will be activated when there is a fault condition			
Surge Test Conditions	Per Class 2 Surge (combination wave)			
Surge let-through voltages	1.2 X 50 μ s, 6kV, 8 X 20 μ s, 3 kA waveform. L-N < 300V			

All * marked voltage regulation ranges are based on 415V nominal output voltage. They would proportionately change in case nominal output voltage is required to be preset at any other value between 380-415V.



TSi Elecpower (P) Ltd

CIB-212, GIDC Industrial Estate,
Waghodia, Vadodara 391760
Gujarat, India

Ph. : +91 2668 262122
info@tsielecpower.com
www.tsielecpower.com

VRp system architecture

